



Not-in-kind approach to remote monitoring in CO2 refrigeration systems

EU GREEN WEEK 2021 PARTNER EVENT

ZERO #EUGreenWeek
POLLUTION
for healthier people and planet




Outline

- The MultiPACK H2020 Project
- 1st MultiPACK demosite: integrated Supermarket in Italy
- Performance evaluation
- Considerations on performances benchmarking

- Refrigerant flow measurement

The MultiPACK Project

- EU funded Horizon 2020 Project (Grant number 723137)
- Duration: 48 months
- Partners: NTNU (coordinator), Sintef, Danfoss, Enex, CNR-ITC, Sonae, RACE
partners are present in all the links of the value chain from initial innovation to the actual end user
- Main focus areas:
 - **Supermarkets**
 - High energy demanding buildings (hotel, gyms, etc.)



What is a MultiPACK unit for Supermarkets?

- A **fully integrated** unit providing Refrigeration, Heating and Air Conditioning based on **Carbon Dioxide** as the refrigerant
- **Heat Pump** functionality
- **Cooling and dehumidification**
- Suitable for **South European Climate**, thanks to **Parallel Compression, Overfed Evaporators, Ejectors** for vapour pre-compression and liquid recirculation
- **Scalable** and **adaptable** to different load ratios and HVAC design
- Fully instrumented for **performances monitoring**

What are MultiPACK objectives for Supermarkets?

- Build up **confidence** for standardised integrated cooling & heating packages
- Demonstrate technical feasibility, reliability and serviceability
- Demonstrate **energy performances** in **South European Climate**


How?

- Installing 3 fully instrumented demo sites

Where?


- **Portugal** and **Italy**

The MultiPACK unit in central Italy



- Nominal capacity 50kW MT, 20 kW LT, 75 kW AC, 110 kW Heating
- Based on a **booster concept** with parallel compression
- Expansion work recovery via **multiejector** system
- Minimised superheat
- Integrated direct air **heating, cooling and dehumidification** with **AHU**
- Heat Pump functionality
- Fully instrumented for performances monitoring

Measurement instruments



- Power input to compressors racks (MT, LT, Aux, Total)
- Refrigerant mass flow MT, MT+LT
- Air flow, T and RH in and out from AHU
- Pressure and temperature for key points state definition
- Components status

Performance evaluation

First law approach

$$COP_{tot} = \frac{\dot{Q}_{MT} + \dot{Q}_{LT} + \dot{Q}_{AC} + \dot{Q}_H}{P_{MT} + P_{LT} + P_{Aux}}$$



$$COP_{MT} = \frac{\dot{Q}_{MT} + (\dot{Q}_{LT} + P_{LT} - \dot{Q}_{ds})}{P_{MT} + P_{Aux}} \quad \text{n.a. if } (\dot{Q}_H > 0 \wedge P_{Aux} > 0)$$

$$COP_{LT} = \frac{\dot{Q}_{LT}}{P_{LT}}$$

Easier evaluation in energy terms



Performance evaluation (winter)



22-23 December 2018

AHU on (heating) during the day

Performance evaluation

Second law approach

$$\eta_{tot} = \frac{P_{C,MT} + P_{C,LT} + P_{C,AC} + P_{C,H}}{P_{MT} + P_{LT} + P_{Aux}} =$$

$$\frac{\dot{Q}_{MT} \left(\frac{T_{amb}}{T_{MT,ref}} - 1 \right) + \dot{Q}_{LT} \left(\frac{T_{amb}}{T_{LT,ref}} - 1 \right) + \dot{Q}_{AC} \left(\frac{T_{amb}}{T_{AC,ref}} - 1 \right) + \dot{Q}_H \left(1 - \frac{T_{amb}}{T_{H,ref}} \right)}{P_{MT} + P_{LT} + P_{Aux}}$$

Requires reference values for $T_{MT,ref}$, $T_{LT,ref}$, $T_{AC,ref}$, $T_{H,ref}$



Assumed as 273.15 K, 251.15 K, 299.15 K and 294.15 K

Performance evaluation

$$LR = \frac{\dot{Q}_{MT}}{\dot{Q}_{LT}}$$

-	-	22/12/2018	22-23/12/2018	12/12/2018	12-13/12/2018
T_{amb}	(°C)	14.5	14.2	10.6	9.9
T_{evMT}	(°C)	-4.6	-5.0	-4.9	-5.1
T_{evLT}	(°C)	-31.3	-30.2	-30.4	-30.9
T_{evaux}	(°C)	2.6	-	-0.8	-
p_{gc}	(10^5 Pa)	70.3	55.8	77.3	53.7
Q_{MT}	(kW)	35.0	24.2	31.4	22.4
Q_{LT}	(kW)	13.4	19.4	16.9	14.5
Q_H	(kW)	30.9	-	49.3	-
LR	(-)	2.6	1.2	1.9	1.5
COP_{MT}	(-)	2.7	5.3	3.2	6.3
COP_{LT}	(-)	3.8	3.7	4.0	4.1
COP_{tot}	(-)	3.6	3.3	4.4	4.0
η_{tot}	(-)	0.20	0.29	0.23	0.27

Performance evaluation-preliminary summer data




21-22 July 2019
AHU on (cooling)

Performance evaluation

- Both 1st and 2nd law approach require loads measurements, i.e. refrigerant flow measurement (not affordable values by direct simple calculation in complex systems)
- Flow meters installation is not common practice in commercial refrigeration
- Objectives: low cost, reliable, good accuracy meter, to be extensively installed in supermarkets


In-house flow meter

- Based on hot wire anemometer principle





Resistor	Nominal Resistance
R_1	500 Ω
R_2	50 Ω
R_x	15 Ω
R_{ptH}	100 Ω
R_{ptT}	1000 Ω

- Expected performance



First prototype



Conclusions

- The MultiPACK H2020 Project
- 1st MultiPACK demosite: **integrated Supermarket** in Italy
- Challenge in **performance measuring**
- Challenge in **performance benchmarking**
- **First or second law** analysis
- **Refrigerant mass flow measurement** is anyhow required for performance evaluation



Thank you!

Silvia MINETTO
silvia.minetto@itc.cnr.it



The MultiPACK Project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 723137

EU GREEN WEEK 2021 PARTNER EVENT