



G E O F I T[®]
SMART GEOTHERMAL

Evaluations of a high-temperature cooling system performance in retrofitting practice of an office building in Mediterranean climate

07/11/19 – Henrikki Pieskä – 1st Nordic ZEB+



This project has received funding from the H2020 programme under Grant Agreement No. 792210



uponor




What is GeoFit?

- Novel geothermal systems, technologies and tools for energy efficient building retrofitting
- Goal: Increase renewable energy use and cut CO₂ emissions in EU building stock through more efficient and economical heating and cooling solutions while improving thermal comfort
 - Targets for LTH and HTC:
 - 12-18% improvements to the COP of GSHP
 - 25% final energy savings by replacing existing H/C components with LTH/HTC components
 - Improved thermal comfort





Pilot Sant Cugat – Constructed 3D Simulation Model





Simulated building

- An office building that is a part of a 3 building complex built in 1975


Parameter	Value
Heated area	288 m ²
Number of occupants	8
Lighting	1.6 W/m ²
Equipment	12 W/m ²
DHW	4 l/person/d
Infiltration	2.7 m ³ /h/m ²





Model validation

- Simulated heating demand compared with measured demand (no data on cooling demand)
- Yearly energy consumption a good match, but big monthly variations
 - Temperature corrected average: 79.6 kWh/m²y
 - Simulated heating: 80.2 kWh/m²y
 - Error < 1%






Studied systems

- Novel HTC system for administrative building compared with building in its current state as a baseline system
- System simulated with various cooling water supply temperatures and ventilation air flows
 - Supply temperatures: 20 °C, 22 °C and 24 °C
 - Supply air flows: 11 l/s/p (ASHRAE), 15 l/s/p (EN15251 CAT III) and 27 l/s/p (EN15251 CAT II)






Comparison of global thermal comfort






Comparison of indoor air quality





Cooling demand



Thank you for your attention



G E O F I T[®]

SMART GEOTHERMAL



uponor