


# Excalibur sport

Phased out - support up till 2029



## Highlights

### Extreme workload range of 8 - 2500 watt

The extraordinary workload range of 8-2500 watt is unique in the world! It makes this ergometer extremely suitable for sports medicine and testing the strongest athletes in the world on their anaerobic power or isokinetic capacity.

### Read out of seating position

The Excalibur Sport has a unique read-out of the seating position on the display of the Control Unit. The display shows saddle height & angle, handlebar position vertical & height.

### Various test modes

Besides the hyperbolic (rpm-independent) mode that is used most of the time, the standard control unit offers several other test modes, like the fixed torque mode and the linear mode. These modes can be used in both manual and terminal mode.

### Heavy Duty Design

The Excalibur Sport is designed for heavy duty sports medicine ergometry, without doing any concession on the esthetic, modern and robust design. In other words: Excalibur Sport: the gold standard in Ergometry!

### Easy to clean

The design of the ergometer and the housing material make it very easy to clean.



# Excalibur sport

Phased out - support up till 2029



The Gold Standard in Ergometry: with proven accuracy and reliability, the Excalibur sport is renowned worldwide as “the gold standard in ergometry”. The newly designed and improved Excalibur sport ergometer meets the latest requirements of modern sports medicine and research. Since athletes are becoming more and more powerful and testing more advanced than ever, this ergometer has been developed for extreme workloads up to 2500 watt! The new design ensures maximum stability at these high workloads. Thanks to the increased adjustability, versatile positioning of the test subject has never been better! The function of this product can be enhanced by using it in combination with our Lode Ergometry Manager software.

## Features

**7  
watt**

### Extreme low start up load

The extreme low start-up load of 7 watts and the adjustability in small steps of 1 watt make this ergometer perfectly suitable for many different applications. The standard control unit shows multiple ergometry parameters and you can determine your specific default setting and start-up menu.



### Designed to be sweat-proof

The housing of the ergometer is designed in such way that sweat does not have the chance to drip into the mechanical parts and cables are protected. This ensures a long lifetime and makes the ergometer insensitive for malfunction.



### LEM compatible

This product can be used with Lode Ergometry Manager (LEM) software to manage data and to apply specific protocols when a Communication card is present



### Adjustable handlebar Excalibur Sport

The position of the handlebar of Excalibur Sport is completely adjustable in height and length



### Adjustable saddle Excalibur Sport

The position of the saddle of the excalibur sport can be adjusted in height, length and angle to suit all users



### Compatible with click pedals

The bicycle ergometer is compatible with most available clickpedals to allow for maximum user flexibility



### Instant maximum load

By selecting P-slope max the ergometer immediately reaches maximum power



### Accurate over a long period of time

The Lode ergometers are supplied with an electro-magnetic braking mechanism of Lanooy (eddy current). The biggest advantage of this braking system compared to a friction braking system is the absolute accuracy and the accuracy over time. Moreover, friction braking systems have more wearing parts.

**1  
watt**

### Small adjustment steps

The workload of the Lode ergometers is adjustable in steps of only 1 watt. Depending on your wishes, the test operator or the test subject can adjust the workload. The steps of 1 watt are possible in the manual mode as well as within protocols.



### Compatible with ECG and pulmonary devices

The Lode ergometers have digital interfaces and can be controlled easily by all known stress ECG and pulmonary devices available in the world. This is one of the reasons why the Lode ergometers are very popular worldwide.

# Excalibur sport

Phased out - support up till 2029



## Changing pedals on a regular base


The standard crank is not intended for regular pedal exchange. If you intend to change pedals regularly, we advise to order the adjustable sports cranks with hardened steel pedal mounting block (part number 925808).

# Excalibur sport

Phased out - support up till 2029




Excalibur sport can a.o be extended with the following options:

<p><b>USB to Serial converter</b></p> <p>Easy connection</p>  <p>Partnumber: 226012</p>	<p><b>Programmable Control Unit with SpO2 &amp; Heart rate</b></p> <p>Measurement of oxygen saturation</p>  <p>Partnumber: 928841</p>	<p><b>Heart rate</b></p> <p>Heart rate controlled cycling</p>  <p>Partnumber: 928826</p>	<p><b>0-Watt start-up system</b></p> <p>Lowest possible startup power</p>  <p>Partnumber: 925805</p>	<p><b>Adjustable sports cranks incl. pediatric range</b></p> <p>Optimal force application</p>  <p>Partnumber: 925808</p>
<p><b>Easy saddle exchange option</b></p> <p>Fast change of saddle to suit all users</p>  <p>Partnumber: 925807</p>	<p><b>Mounting Bracket Control Unit &amp; RPM meter</b></p> <p>All controls at hand</p>  <p>Partnumber: 928848</p>	<p><b>Excalibur sport rebuilt to Excalibur sport PFM</b></p> <p>Upgrade your Excalibur Sport to the max</p>  <p>Partnumber: 925880</p>	<p><b>Mounting Bracket Control Unit</b></p> <p>More controls at hand</p>  <p>Partnumber: 928849</p>	<p><b>Programmable Control Unit</b></p> <p>Programming protocols in advance</p>  <p>Partnumber: 928811</p>
<p><b>RS232 cable</b></p> <p>Easy connection</p>  <p>Partnumber: 930911</p>	<p><b>Saddle for children</b></p> <p>Versatile ergometry</p>  <p>Partnumber: 401066</p>	<p><b>Saddle for children - ordered additionally</b></p> <p>Versatile ergometry</p>  <p>Partnumber: P401066</p>	<p><b>Bluetooth Smart heart rate</b></p> <p>Heartrate available within an extreme wide</p>  <p>Partnumber: 945833</p>	

# Excalibur sport

Phased out - support up till 2029



## Specifications

### Workload

Minimum load	8 W
Maximum peak load	2500 W
Isokinetic workload control	✓
Minimum load increments	1 W
Maximum continuous load	1500 W
Hyperbolic workload control	✓
Linear workload control	✓
Fixed torque workload control	✓
Maximum rpm independent constant load	180 rpm
Minimum rpm independent constant load	25 rpm
Optional heart rate controlled workload	✓
Electromagnetic "eddy current" braking system	✓
Dynamic calibration	✓

### Accuracy

Workload accuracy below 100 W	2 W
Workload accuracy over 1500 W	5 %
Workload accuracy from 100 to 1500 W	2 %

### Comfort

Toeclips on pedals	✓	
Q-factor	147 mm	
Minimum leg length user	725 mm	28.5 inch
Minimum leg length user (incl. adjustable pedals)	650 mm	25.6 inch
Vertical seat adjustment maximum	938 mm	36.9 inch
Vertical seat adjustment minimum	550 mm	21.7 inch
Horizontal seat adjustment minimum	72 mm	2.8 inch
Horizontal seat adjustment maximum	324 mm	12.8 inch
Seat angle adjustment maximum	10 °	
Allowed user weight	180 kg	396.8 lbs
Horizontal handlebar adjustment minimum	229 mm	9 inch
Horizontal handlebar adjustment maximum	600 mm	23.6 inch
Vertical handlebar adjustment minimum	465 mm	18.3 inch
Vertical handlebar adjustment maximum	855 mm	33.7 inch
Handlebar adjustment angle	360 °	

### Certification

CE class Im according to MDD93/42/EEC	✓
CE class of product with optional SpO2	Ila
CE class of product with optional BPM	Ila
CB according to IECEE CB	✓

### Order info

### User Interface

Readout Distance	✓
Readout RPM	✓
Readout Heartrate	✓
Readout target HR	✓
Readout Energy	✓
Readout Torque	✓
Readout Time	✓
Readout Power	✓
Set Display	✓
Set Resistance	✓
Set P-Slope	✓
Set Mode	✓
Manual operation mode	✓
Preset protocol operation mode	✓
Analog operation mode	✓
Terminal operation mode	✓
External control unit	✓
Selfdesigned protocol operation mode	✓

### Connectivity

Analog connector	✓
RS232 in connector	✓
RS232 out connector	✓

### Dimensions

Product length (cm)	130 cm	51.2 inch
Product width (cm)	70 cm	27.6 inch
Product height	89 cm	35 inch
Product weight	100 kg	220.5 lbs

### Power requirements

Power cord length	250 cm	98.4 inch
Power cord IEC 60320 C13 with CEE 7/7 plug	✓	
Power cord NEMA	✗	
115 V AC 50/60 Hz (130 VA)	✓	
230 V AC 50/60 Hz (130 VA)	✓	

### Standards & Safety

IEC 60601-1:2005	✓
ISO 13485:2016 compliant	✓
ISO 9001:2015 compliant	✓

# Excalibur sport

Phased out - support up till 2029



Partnumber: 925900

*\*Specifications are subject to change without notice.*